

Appln No. 10/047,535

Amdt date September 20, 2005

Reply to Office action of August 8, 2005

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Original) A method performed by a computer for generating a geometric pattern from an image having a plurality of ridges and mesh points, the method comprising the steps of:

forming a partial differential equation by transferring values for positions in the image to corresponding coefficients of the partial differential equation;

determining simultaneous difference equations corresponding to the partial differential equation and the image mesh points;

solving the simultaneous difference equations; and

mapping the solutions of the simultaneous difference equations to respective positions on the image to determine features of the image.

2. (Original) The method of claim 1, wherein the image is a fingerprint.

3. (Original) The method of claim 1, wherein the image is a facial image.

4. (Original) The method of claim 1, wherein the image is a hand-palm image.

5. (Original) The method of claim 1, wherein the image is an eye iris image.

Appln No. 10/047,535

Amdt date September 20, 2005

Reply to Office action of August 8, 2005

6. (Original) The method of claim 1, wherein the image is a texture image.

7. (Original) The method of claim 1, wherein the image is an eye retina image.

8. (Original) The method of claim 1, wherein the step of forming a partial differential equation comprises the steps of:

calculating a plurality of intrinsic properties of the image according to image ridge pattern;

mapping the plurality of intrinsic properties into coefficients of the partial differential equation; and

determining a boundary condition for the partial differential equation from the image to establish a relationship between properties of the image and the partial differential equation.

9. (Original) The method of claim 1, wherein the step of determining simultaneous difference equations comprises the step of replacing each derivative and variable items of the partial differential equation with respect to each mesh point in the image.

10. (Original) The method of claim 1, wherein the step of forming a partial differential equation comprises the steps of:

determining initial conditions for the partial differential equation; and

determining boundary condition for the partial differential equation.

11. (Original) The method of claim 10, wherein the step of determining initial conditions comprises the steps of:

Appln No. 10/047,535

Amdt date September 20, 2005

Reply to Office action of August 8, 2005

normalizing the image to reduce variations in gray-level values along ridges of the image;
estimating property values of the image; and
mapping the estimated property values into weight coefficients of the partial differential equation.

12. (Original) The method of claim 10, wherein the step of determining boundary condition comprises the steps of:
drawing a close boundary within the image; and
setting boundary condition on the drawn boundary.

13. (Original) The method of claim 11, wherein the step of normalizing comprises the steps of:
determining M, mean of the gray-level in a region R by computing

$$M = (1/N) \sum_{(I,J) \in R} F(I,J) \quad (2a)$$

where N is total number pixels in the region R; F(I, J) is gray value of the image at point (I, J);
determining V, variance of the region R by computing

$$V = (1/N) \sum_{(I,J) \in R} (F(I,J) - M)^2 \quad (2b); \text{ and}$$

determining a normalized region R by computing

$$\begin{aligned} R(I,J) &= m + \sqrt{(v * (F(I,J) - M) * (F(I,J) - M)) / V}, \text{ if } (I,J) > M; \\ R(I,J) &= m - \sqrt{(v * (F(I,J) - M) * (F(I,J) - M)) / V}, \text{ otherwise} \end{aligned} \quad (2c)$$

where m and v are the desired mean and variance values, respectively.

Appln No. 10/047,535

Amdt date September 20, 2005

Reply to Office action of August 8, 2005

14. (Currently Amended) The method of claim 11, wherein the step of estimating property values comprises the steps of:
dividing a region R into blocks of size b*b as B(k);
computing gradients at each pixel in R as

$$\begin{aligned}\partial_x(I,J) &= (p1 * F(I-d,J) + p2 * F(I,J) + p3 * (F(I+d,J)))/p, \\ \partial_y(I,J) &= (p1 * F(I,J-d) + p2 * F(I,J) + p3 * (F(I,J+d)))/p\end{aligned}\tag{3a}$$

where (I, J) and (I, J) are the gradient magnitude in x and y directions at pixel (I, J) of the image respectively, p1, p2 are positive numbers, p3 is negative number, and d is a constant expressed as step of the gradients $p = p1 + p2 + p3$;

estimating local orientation of each block (B(k)) centered at pixel (I, J) by computing

$$\xi_x(I,J) = \sum_{(u,v) \in B(k)} \sum 2 * \partial_x(u,v) * \partial_y(u,v),\tag{3b}$$

$$\zeta_y(I,J) = \sum_{(u,v) \in B(k)} \sum (\partial_x(u,v) * \partial_y(u,v)),\tag{3c}$$

$$\theta(I,J) = (1/2) \text{atan}\{\xi_x(I,J)/\zeta_y(I,J)\}\tag{3d}$$

Where $\theta(I,J)$ is an estimate of the local ridge orientation at the block centered at pixel (I, J);

computing ridge oriental vector as

$$P = (1/n) \sum_{(I,J) \in R} \cos(2 * \theta(I,J))\tag{4a}$$

Appln No. 10/047,535

Amdt date September 20, 2005

Reply to Office action of August 8, 2005

$$Q = (1/n) \sum_{(I,J) \in R} \sin(2 * \theta(I,J)) \quad (4b)$$

where P and Q are first and second components of the ridge oriental vector, respectively, and n is the total number of pixels calculated at the local region R;

for each block centered at pixel (I, J), computing the minimal value and maximal value the pixel;

for each block centered at pixel (I, J), computing a sequence of pixels seq(I, J) that take minimal and maximal value along the direction (a, b), where (a, b) is orthogonal vector of the main oriental vector (p, q);

computing freq(I, J), frequency of seq(I, J) at each block centered at pixel (I, J) according to the differential value between connected elements in seq(I, J); and

estimating a local ridge frequency W by computing

$$W = (1/K) \sum \sum_{(u,v) \in \text{wnd}(I,J)} \text{freq}(u,v) \quad (5)$$

15. (Original) The method of claim 11, wherein the step of mapping comprises the step of determining weight coefficients, A1, A2, A3, A4, A5 and A6 of a partial differential equation

$$A1 \frac{\partial^2 U}{\partial X^2} + A2 \frac{\partial^2 U}{\partial X \partial Y} + A3 \frac{\partial^2 U}{\partial Y^2} + A4 \frac{\partial U}{\partial X} + A5 \frac{\partial U}{\partial Y} + A6 * U = 0 \quad (1)$$

by computing

$$A1 = P * P * (P * P + Q * Q) * W * W, \quad (6a)$$

$$A2 = 2 * (\text{sqrt}(u * u - P * P * W * W) * \text{sqrt}(v - Q * Q * W * W)) / W, \quad (6b)$$

$$A3 = Q * Q * (P * P + Q * Q) * W * W, \quad (6c)$$

Appln No. 10/047,535

Amdt date September 20, 2005

Reply to Office action of August 8, 2005

$$A4 = u * q + v, \quad (6d)$$

$$A5 = -v * p - u, \text{ and} \quad (6e)$$

$$A6 = a * (P * P + Q * Q) + b \quad (6f)$$

where a, b, u, v are constants.

16. (Original) The method of claim 12, wherein the step of setting boundary condition comprises the steps of:

denoting B as a discrete boundary in a region R; and
computing

$$\left. U \right|_{(x,y) \in S} = B1(x,y), \quad \left. \frac{\partial U}{\partial s} \right|_{(x,y) \in S} = B2(x,y) \quad (7)$$

where S is a continuous boundary defined on the discrete boundary B, and B1(x, y) and B2(x, y) are the continuous function and differentiable function defined on the boundary S, respectively.

17. (Original) The method of claim 1, wherein the step of determining simultaneous difference equations comprises the steps of:

integralizing the image to produce a group of integral points within a region R and an integral boundary IB;

discretizing the image based on the mesh points for numerating the partial differential equation and a boundary condition; and

transforming the discretized image by solving each mesh point in the image to determine the simultaneous difference equations.

18. (Original) The method of claim 17, wherein the step of integralizing comprises the steps of:

Appln No. 10/047,535

Amdt date September 20, 2005

Reply to Office action of August 8, 2005

denoting two directions of the coordinate axes of the fingerprint image as X-direction and Y-direction; and

along the X-direction and Y-direction, computing integral points at a desired step length H as follow

$$X(I) = X0 + I*H, \quad I = 0, 1, 2, \dots, W(F), \quad (8a)$$

$$Y(J) = Y0 + J*H, \quad J = 0, 1, 2, \dots, H(F), \quad (8b)$$

where, (X0, Y0) is top left point of the image, W(F) is the width of the image and H(F) is the height of the image.

19. (Currently Amended) The method of claim 17, wherein the step of discretizing comprises the steps of:

computing the derivatives in the partial differential equation

$$A1 \frac{\partial^2 U}{\partial X^2} + A2 \frac{\partial^2 U}{\partial X \partial Y} + A3 \frac{\partial^2 U}{\partial Y^2} + A4 \frac{\partial U}{\partial X} + A5 \frac{\partial U}{\partial Y} + A6 * U = 0 \quad (1)$$

with respect to each inner mesh point as

$$\frac{\partial U}{\partial X} \approx [U(X+H, Y) - U(X, Y)]/H \quad (9a)$$

$$\frac{\partial U}{\partial Y} \approx [U(X, Y+H) - U(X, Y)]/H \quad (9b)$$

$$\frac{\partial^2 U}{\partial X^2} \approx [U(X+H, Y) - 2*U(X, Y) + U(X-H, Y)]/(H*H) \quad (9c)$$

$$\frac{\partial^2 U}{\partial Y^2} \approx [U(X, Y+H) - 2*U(X, Y) + U(X, Y-H)]/(H*H) \quad (9d)$$

$$\frac{\partial^2 U}{\partial X \partial Y} \approx [U(X+H, Y+H) - U(X+H, Y) - U(X, Y+H) + U(X, Y)]/(H*H) \quad (9e)$$

where (X, Y) is inner mesh point in region R, IMP(R);

Appln No. 10/047,535

Amdt date September 20, 2005

Reply to Office action of August 8, 2005

discretizing the boundary condition

$$U \Big|_{(x,y) \in S} = B1(x,y), \quad \frac{\partial U}{\partial s} \Big|_{(x,y) \in S} = B2(x,y) \quad ; \text{ and} \quad (7)$$

combining the numerical derivatives of the partial differential equation and numerical boundary condition.

20. (Original) The method of claim 19, wherein the step of discretizing the boundary condition comprises the steps of:

replacing the continuous function $U(X, Y)$ in the boundary condition with discrete function $F(I, J)$, wherein (I, J) is inner mesh point of a region in the image;

replacing the continuous function $B1(x, y)$ in the boundary condition with a numerical function according to

$$D1(X,Y) = f1 * F(X,Y) + f2, \quad (X,Y) \in IB \quad (10)$$

where $f1$ and $f2$ are constants that are predetermined according to brightness and contrast of the image, and $F(X, Y)$ is the gray value at point (X, Y) on the integral boundary IB ; and

replacing the continuous function $B2(x, y)$ in the boundary condition with a numerical function according to

$$\begin{aligned} D2(X,Y) &= f1 * [F(X1,Y1) - F(X,Y)] / h, & (X,Y) \in IB \\ h &= \text{sqrt}((X1-X)*(X1-X) + (Y1-Y)*(Y1-Y)); \end{aligned} \quad (11)$$

where $(X1, Y1)$ is an integral point on IB selected as the next adjacent point along the boundary line IB .

Appln No. 10/047,535

Amdt date September 20, 2005

Reply to Office action of August 8, 2005

21. (Original) The method of claim 1, wherein the step of mapping the solutions comprises the steps of:

for each region R, computing minimum value min (R) and maximum value max (R) in the solution;

computing ratio value $r(R) = 255 / (\max(R) - \min(R))$;

for each point (I, J) in the region R, assigning $v(I, J) * 3$ as the solution at point (I, J);

computing $W(I, J) = r(R) * (v(I, J) - \min(R))$ as the mapping of $w(I, J)$ into gray level byte at the position (I, J); and

enhancing the region R is by placing the value $W(I, J)$ at position (I, J).

22. (Canceled)

23. (Currently Amended) The A method of claim 22 performed by a computer for extracting features from an image, the method comprising the steps of:

establishing a mathematical model according to regional conditions in the image;

converting the mathematical model into numerical equations;

solving the numerical equations; and

mapping respective values of the solutions of the numerical equations to respective regions of the image, wherein the step

of establishing a mathematical model comprises the steps of:

forming a partial differential equation;

calculating a plurality of intrinsic properties of the image according to image ridge pattern;

mapping the plurality of intrinsic properties into coefficients of the partial differential equation; and

determining a boundary condition for the partial differential equation from the image to establish a relationship

Appln No. 10/047,535

Amdt date September 20, 2005

Reply to Office action of August 8, 2005

between properties of the image and the partial differential equation.

24. (Canceled)

25. (Canceled)

26. (Currently Amended) The method of claim [[24]] 23, wherein the step of determining boundary condition comprises the steps of:

drawing a close boundary within the image; and
setting boundary condition on the drawn boundary.

27 - 29. (Canceled)

30. (Original) The method of claim 26, wherein the step of setting boundary condition comprises the steps of:

denoting B as a discrete boundary in a region R; and
computing

$$\left. U \right|_{(x,y) \in S} = B1(x,y), \quad \left. \frac{\partial U}{\partial s} \right|_{(x,y) \in S} = B2(x,y) \quad (7)$$

where S is a continuous boundary defined on the discrete boundary B, and B1(x, y) and B2(x, y) are the continuous function and differentiable function defined on the boundary S, respectively.

31 - 34. (Canceled)

Appln No. 10/047,535

Amdt date September 20, 2005

Reply to Office action of August 8, 2005

35. (Currently Amended) The method of claim [[22]] 23, wherein the step of ~~transferring~~ mapping respective values of the solutions comprises the steps of:

for each region R in the image, computing minimum value min (R) and maximum value max (R) in the solution;
computing ratio value $r(R) = 255 / (\max(R) - \min(R))$;
for each point (I, J) in the region R, assigning $v(I, J) * 3$ as the solution at point (I, J);
computing $W(I, J) = r(R) * (v(I, J) - \min(R))$ as the mapping of $w(I, J)$ into gray level byte at the position (I, J); and
enhancing the region R is by placing the value $W(I, J)$ at position (I, J).

36. (Currently Amended) The method of claim [[22]] 23, wherein the image is one or more of a fingerprint image, a facial image, a hand-palm image, an eye iris, an eye retina, and a texture image.

37. (Original) A digital signal processor (DSP) having stored thereon a set of instructions including instructions for generating geometric pattern from an image having a plurality of ridges and mesh points, when executed, the instructions cause the DSP to perform the steps of:

forming a partial differential equation by transferring values for positions in the image to corresponding coefficients of the partial differential equation;

determining simultaneous difference equations corresponding to the partial differential equation and the image mesh points;

solving the simultaneous difference equations; and

mapping the solutions of the simultaneous difference equations to respective positions on the image to determine features of the image.

Appln No. 10/047,535

Amdt date September 20, 2005

Reply to Office action of August 8, 2005

38. (Original) The DSP of claim 37, wherein the step of forming a partial differential equation comprises the steps of:
determining initial conditions for the partial differential equation; and

determining boundary condition for the partial differential equation.

39. (Original) The DSP of claim 38, wherein the step of determining initial conditions comprises the steps of:

normalizing the image to reduce variations in gray-level values along ridges of the image;

estimating property values the image; and

mapping the estimated property values into weight coefficients of the partial differential equation.

40. (Original) The DSP of claim 38, wherein the step of determining boundary condition comprises the steps of:

drawing a close boundary within the image; and

setting boundary condition on the drawn boundary.

41. (Original) The DSP of claim 39, wherein the step of normalizing comprises the steps of:

determining M, mean of the gray-level in a region R by computing

$$M = (1/N) \sum_{(I,J) \in R} F(I,J) \quad (2a)$$

where N is total number pixels in the region R; F(I, J) is gray value of the image at point (I, J);

determining V, variance of the region R by computing

Appln No. 10/047,535

Amdt date September 20, 2005

Reply to Office action of August 8, 2005

$$V = (1/N) \sum_{(I,J) \in R} \sum (F(I,J) - M(F)) * (F(I,J) - M(F)) \quad (2b); \text{ and}$$

determining a normalized region R by computing

$$\begin{aligned} R(I,J) &= m + \sqrt{(v * (F(I,J) - M) * (F(I,J) - M)) / V}, \text{ if } (I,J) > M; \\ R(I,J) &= m - \sqrt{(v * (F(I,J) - M) * (F(I,J) - M)) / V}, \text{ otherwise} \end{aligned} \quad (2c)$$

where m and v are the desired mean and variance values, respectively.

42. (Currently Amended) The DSP of claim 39, wherein the step of estimating property values comprises the steps of:
dividing a region R into blocks of size b*b as B(k);
computing gradients at each pixel in R as

$$\begin{aligned} \partial x(I,J) &= (p1 * F(I-d,J) + p2 * F(I,J) + p3 * (F(I+d,J))) / p, \\ \partial y(I,J) &= (p1 * F(I,J-d) + p2 * F(I,J) + p3 * (F(I,J+d))) / p \end{aligned} \quad (3a)$$

where (I, J) and (I, J) are the gradient magnitude in x and y directions at pixel (I, J) of the image respectively, p1, p2 are positive numbers, [[p2]] p3 is negative number, and d is a constant expressed as step of the gradients $p = p1 + p2 + p3$;

estimating local orientation of each block (B(k)) centered at pixel (I, J) by computing

$$\xi_x(I,J) = \sum \sum_{(u,v) \in B(k)} 2 * \partial x(u,v) * \partial y(u,v), \quad (3b)$$

$$\xi_y(I,J) = \sum \sum_{(u,v) \in B(k)} (\partial \partial x(u,v) * \partial \partial y(u,v)), \quad (3c)$$

$$\theta(I,J) = (1/2) \text{atan} \{ \xi_x(I,J) / \xi_y(I,J) \} \quad (3d)$$

Appln No. 10/047,535

Amdt date September 20, 2005

Reply to Office action of August 8, 2005

Where $\theta(I, J)$ is an estimate of the local ridge orientation at the block centered at pixel (I, J) ;

computing ridge oriental vector as

$$P = (1/n) \sum_{(I,J) \in R} \cos(2 * \theta(I,J)) \quad (4a)$$

$$Q = (1/n) \sum_{(I,J) \in R} \sin(2 * \theta(I,J)) \quad (4b)$$

Where P and Q are first and second components of the ridge oriental vector, respectively, and n is the total number of pixels calculated at the local region R ;

for each block centered at pixel (I, J) , computing the minimal value and maximal value the pixel;

for each block centered at pixel (I, J) , computing a sequence of pixels $seq(I, J)$ that take minimal and maximal value along the direction (a, b) , where (a, b) is orthogonal vector of the main oriental vector (p, q) ;

computing $freq(I, J)$, frequency of $seq(I, J)$ at each block centered at pixel (I, J) according to the differential value between connected elements in $seq(I, J)$; and

estimating a local ridge frequency W by computing

$$W = (1/K) \sum \sum_{(u,v) \in wnd(I,J)} freq(u,v) \quad (5)$$

Appln No. 10/047,535

Amdt date September 20, 2005

Reply to Office action of August 8, 2005

43. (Original) The DSP of claim 39, wherein the step of mapping comprises the step of determining weight coefficients, A1, A2, A3, A4, A5 and A6 of a partial differential equation

$$A1 \frac{\partial^2 U}{\partial X^2} + A2 \frac{\partial^2 U}{\partial X \partial Y} + A3 \frac{\partial^2 U}{\partial Y^2} + A4 \frac{\partial U}{\partial X} + A5 \frac{\partial U}{\partial Y} + A6 * U = 0 \quad (1)$$

by computing

$$A1 = P * P * (P * P + Q * Q) * W * W, \quad (6a)$$

$$A2 = 2 * (\text{sqrt}(u * u - P * P * W * W) * \text{sqrt}(v - Q * Q * W * W)) / W, \quad (6b)$$

$$A3 = Q * Q * (P * P + Q * Q) * W * W, \quad (6c)$$

$$A4 = u * q + v, \quad (6d)$$

$$A5 = -v * p - u, \text{ and} \quad (6e)$$

$$A6 = a * (P * P + Q * Q) + b \quad (6f)$$

where a, b, u, v are constants.

44. (Original) The DSP of claim 40, wherein the step of setting boundary condition comprises the steps of:

denoting B as a discrete boundary in a region R; and
computing

$$\left. U \right|_{(x,y) \in S} = B1(x,y), \quad \left. \frac{\partial U}{\partial s} \right|_{(x,y) \in S} = B2(x,y) \quad (7)$$

where S is a continuous boundary defined on the discrete boundary B, and B1(x, y) and B2(x, y) are the continuous function and differentiable function defined on the boundary S, respectively.

Appln No. 10/047,535

Amdt date September 20, 2005

Reply to Office action of August 8, 2005

45. (Original) The DSP of claim 37, wherein the step of determining simultaneous difference equations comprises the steps of:

integralizing the image to produce a group of integral points within a region R and an integral boundary IB;

discretizing the image based on the mesh points for numerating the partial differential equation and a boundary condition; and

transforming the discretized image by solving each mesh point in the image to determine the simultaneous difference equations.

46. (Original) The DSP of claim 45, wherein the step of integralizing comprises the steps of:

denoting two directions of the coordinate axes of the fingerprint image as X-direction and Y-direction; and

along the X-direction and Y-direction, computing integral points at a desired step length H as follow

$$X(I) = X_0 + I \cdot H, \quad I = 0, 1, 2, \dots, W(F), \quad (8a)$$

$$Y(J) = Y_0 + J \cdot H, \quad J = 0, 1, 2, \dots, H(F), \quad (8b)$$

where, (X_0, Y_0) is top left point of the image, $W(F)$ is the width of the image and $H(F)$ is the height of the image.

47. (Currently Amended) The DSP of claim 45, wherein the step of discretizing comprises the steps of:

computing the derivatives in the partial differential equation

$$A_1 \frac{\partial^2 U}{\partial X^2} + A_2 \frac{\partial^2 U}{\partial X \partial Y} + A_3 \frac{\partial^2 U}{\partial Y^2} + A_4 \frac{\partial U}{\partial X} + A_5 \frac{\partial U}{\partial Y} + A_6 \cdot U = 0 \quad (1)$$

with respect to each inner mesh point as

Appln No. 10/047,535

Amdt date September 20, 2005

Reply to Office action of August 8, 2005

$$\frac{\partial U}{\partial X} \approx [U(X+H, Y) - U(X, Y)]/H \quad (9a)$$

$$\frac{\partial U}{\partial Y} \approx [U(X, Y+H) - U(X, Y)]/H \quad (9b)$$

$$\frac{\partial^2 U}{\partial X^2} \approx [U(X+H, Y) - 2*U(X, Y) + U(X-H, Y)]/(H*H) \quad (9c)$$

$$\frac{\partial^2 U}{\partial Y^2} \approx [U(X, Y+H) - 2*U(X, Y) + U(X, Y-H)]/(H*H) \quad (9d)$$

$$\frac{\partial^2 U}{\partial X \partial Y} \approx [U(X+H, Y+H) - U(X+H, Y) - U(X, Y+H) + U(X, Y)]/(H*H) \quad (9e)$$

where (X, Y) is inner mesh point in region R, IMP(R);

discretizing the boundary condition

$$U|_{(x,y) \in S} = B1(x,y), \quad \frac{\partial U}{\partial s}|_{(x,y) \in S} = B2(x,y) \quad ; \text{ and} \quad (7)$$

combining the numerical derivatives of the partial differential equation and numerical boundary condition.

48. (Original) The DSP of claim 47, wherein the step of discretizing the boundary condition comprises the steps of:

replacing the continuous function U(X, Y) in the boundary condition with discrete function F(I, J), wherein (I, J) is inner mesh point of a region in the image;

replacing the continuous function B1(x, y) in the boundary condition with a numerical function according to

$$D1(X, Y) = f1 * F(X, Y) + f2, \quad (X, Y) \in IB \quad (10)$$

Appln No. 10/047,535

Amdt date September 20, 2005

Reply to Office action of August 8, 2005

where f_1 and f_2 are constants that are predetermined according to brightness and contrast of the image, and $F(X, Y)$ is the gray value at point (X, Y) on the integral boundary IB ; and

replacing the continuous function $B_2(x, y)$ in the boundary condition with a numerical function according to

$$\begin{aligned} D_2(X, Y) &= f_1 * [F(X_1, Y_1) - F(X, Y)] / h, & (X, Y) \in IB \\ h &= \text{sqrt}((X_1 - X) * (X_1 - X) + (Y_1 - Y) * (Y_1 - Y)); \end{aligned} \quad (11)$$

where (X_1, Y_1) is an integral point on IB selected as the next adjacent point along the boundary line IB .

49. (Original) The DSP of claim 37, wherein the step of mapping the solutions comprises the steps of:

for each region R , computing minimum value $\min(R)$ and maximum value $\max(R)$ in the solution;

computing ratio value $r(R) = 255 / (\max(R) - \min(R))$;

for each point (I, J) in the region R , assigning $v(I, J) * 3$ as the solution at point (I, J) ;

computing $W(I, J) = r(R) * (v(I, J) - \min(R))$ as the mapping of $w(I, J)$ into gray level byte at the position (I, J) ; and

enhancing the region R is by placing the value $W(I, J)$ at position (I, J) .

50. (Original) The DSP of claim 37, wherein the image is one or more of a finger print, a facial image, a hand-palm image, an eye iris, an eye retina, and a texture image.

51 - 55. (Cancelled)

Appln No. 10/047,535

Amdt date September 20, 2005

Reply to Office action of August 8, 2005

56. (Currently Amended) The A method of claim 51 performed by a computer for biometric image processing, the DSP comprising the steps of:

establishing numerical relationship between visual appearance of the biometric image and a partial differential equation model of the image; and

approximating solutions of the partial differential equation with a boundary condition according to the established numerical relationship to determine features of the biometric image, wherein the step of approximating solutions comprises the steps of:

integralizing the image to produce a group of integral points within a region R and an integral boundary IB;

discretizing the image based on mesh points for numerating a partial differential equation and a boundary condition;

transforming the discretized image by solving each mesh point in the image to determine the simultaneous difference equations;

replacing the continuous function $U(X, Y)$ in the boundary condition with discrete function $F(I, J)$, wherein (I, J) is inner mesh point of a region in the image;

replacing the continuous function $B1(x, y)$ in the boundary condition with a numerical function according to

$$D1(X,Y)=f1*F(X,Y)+f2, \quad (X,Y) \in IB \quad (10)$$

where $f1$ and $f2$ are constants that are predetermined according to brightness and contrast of the image, and $F(X, Y)$ is the gray value at point (X, Y) on the integral boundary IB; and

replacing the continuous function $B2(x, y)$ in the boundary condition with a numerical function according to

Appln No. 10/047,535

Amdt date September 20, 2005

Reply to Office action of August 8, 2005

$$\begin{aligned} D2(X,Y) &= f1*[F(X1,Y1)-F(X,Y)]/h, & (X,Y) \in IB \\ h &= \text{sqrt}((X1-X)*(X1-X)+(Y1-Y)*(Y1-Y)); \end{aligned} \quad (11)$$

where (X1, Y1) is an integral point on IB selected as the next adjacent point along the boundary line IB.

57. (Original) The method of claim 56, wherein the step of integralizing comprises the steps of:

denoting two directions of the coordinate axes of the fingerprint image as X-direction and Y-direction; and

along the X-direction and Y-direction, computing integral points at a desired step length H as follow

$$X(I) = X0 + I*H, \quad I = 0, 1, 2, \dots, W(F), \quad (8a)$$

$$Y(J) = Y0 + J*H, \quad J = 0, 1, 2, \dots, H(F), \quad (8b)$$

where, (X0, Y0) is top left point of the image, W(F) is the width of the image and H(F) is the height of the image.

58. (Currently Amended) The method of claim 56, wherein the step of discretizing comprises the steps of:

computing the derivatives in the partial differential equation

$$A1 \frac{\partial^2 U}{\partial X^2} + A2 \frac{\partial^2 U}{\partial X \partial Y} + A3 \frac{\partial^2 U}{\partial Y^2} + A4 \frac{\partial U}{\partial X} + A5 \frac{\partial U}{\partial Y} + A6 * U = 0 \quad (1)$$

with respect to each inner mesh point as

$$\frac{\partial U}{\partial X} \approx [U(X+H, Y) - U(X, Y)]/H \quad (9a)$$

$$\frac{\partial U}{\partial Y} \approx [U(X, Y+H) - U(X, Y)]/H \quad (9b)$$

Appln No. 10/047,535

Amdt date September 20, 2005

Reply to Office action of August 8, 2005

$$\frac{\partial^2 U}{\partial X^2} \approx [U(X+H, Y) - 2*U(X, Y) + U(X-H, Y)]/(H*H)$$

$$\frac{\partial^2 U}{\partial X^2} \approx [U(X+H, Y) - 2*U(X, Y) + U(X-H, Y)]/(H*H) \quad (9c)$$

$$\frac{\partial^2 U}{\partial Y^2} \approx [U(X, Y+H) - 2*U(X, Y) + U(X, Y-H)]/(H*H) \quad (9d)$$

$$\frac{\partial^2 U}{\partial X \partial Y} \approx [U(X+H, Y+H) - U(X+H, Y) - U(X, Y+H) + U(X, Y)]/(H*H) \quad (9e)$$

where (X, Y) is inner mesh point in region R, IMP(R);

discretizing the boundary condition

$$U|_{(x,y) \in S} = B1(x,y), \quad \frac{\partial U}{\partial s}|_{(x,y) \in S} = B2(x,y) \quad ; \text{ and} \quad (7)$$

combining the numerical derivatives of the partial differential equation and numerical boundary condition.

59. (Original) The method of claim 56, wherein the step of discretizing the boundary condition comprises the steps of:

replacing the continuous function U(X, Y) in the boundary condition with discrete function F(I, J), wherein (I, J) is inner mesh point of a region in the image;

replacing the continuous function B1(x, y) in the boundary condition with a numerical function according to

$$D1(X, Y) = f1 * F(X, Y) + f2, \quad (X, Y) \in IB \quad (10)$$

where f1 and f2 are constants that are predetermined according to brightness and contrast of the image, and F(X, Y) is the gray value at point (X, Y) on the integral boundary IB; and

Appln No. 10/047,535

Amdt date September 20, 2005

Reply to Office action of August 8, 2005

replacing the continuous function $B2(x, y)$ in the boundary condition with a numerical function according to

$$\begin{aligned} D2(X, Y) &= f1 * [F(X1, Y1) - F(X, Y)] / h, & (X, Y) \in IB \\ h &= \text{sqrt}((X1 - X) * (X1 - X) + (Y1 - Y) * (Y1 - Y)); \end{aligned} \quad (11)$$

where $(X1, Y1)$ is an integral point on IB selected as the next adjacent point along the boundary line IB.

60. (Original) The method of claim 56, further comprising the step of mapping the solutions of the partial differential equation to respective positions on the image to determine features of the image.

61. (Original) The method of claim 60, wherein the step of mapping the solutions comprises the steps of:

for each region R, computing minimum value $\min(R)$ and maximum value $\max(R)$ in the solution;

computing ratio value $r(R) = 255 / (\max(R) - \min(R))$;

for each point (I, J) in the region R, assigning $v(I, J) * 3$ as the solution at point (I, J) ;

computing $W(I, J) = r(R) * (v(I, J) - \min(R))$ as the mapping of $w(I, J)$ into gray level byte at the position (I, J) ; and

enhancing the region R is by placing the value $W(I, J)$ at position (I, J) .

62. (Currently Amended) The method of claim [[51]] 56, wherein the image is one or more of a finger print, a facial image, a hand-palm image, an eye iris, an eye retina, and a texture image.